


CUSTOMER DATASHEET


Printed: 11/02/2022


Product Management
Transportation Europe

Central Article Code: DB9095W02-A Created: 06/09/2005

Local Code: TG1705 Modified: 01/06/2020







Final Outlook DB902-A Approval date 01/10/2005

D		D	a	D	N/	IΑ	N	\mathbf{c}		C
	_	•	 _		IV			u	_	

Voltage (V): 12 V

C20 (Ah): 170.0 20 h Cranking (A): 950 EN

Charge: WET

Technology: Vented/Flooded

Grid: Hybrid

Vibration: V2 (30Hz+/-2Hz/6g/2h)

Endurance: E2 (90 cycles@50%)

CONTAINER

Type: DB9 BLACK Hold Down: B3

H.D. Adapter: No

COVER

Type: DIN BLACK

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 514

 Width (mm \pm 2):
 218

 Height (mm \pm 2):
 210

 Total Weight (kg \pm 5%):
 42.50

Type: 6 x M27

BLACK

HANDLES

PLUGS

Type: 2 x Rope (Rigid holder) BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.