


## **CUSTOMER DATASHEET**


Printed: 11/02/2022


Product Management
Transportation Europe

Central Article Code: D09100C01-A Created: 27/04/2012

Local Code: TG1806 Modified: 31/07/2020







Final Outlook D0901-A Approval date 15/05/2010

## **PERFORMANCES CONTAINER** Voltage (V): 12 V D09 **BLACK** Type: B3 Hold Down: C20 (Ah): 180.0 20 h H.D. Adapter: No ΕN 1000 Cranking (A): WET Charge: **COVER** Vented/Flooded Technology: Type: Flat/Screw BLACK Grid: Polarity: ETN 4 Ca/Ca Vibration: Terminals: EN taper post V2 (30Hz+/-2Hz/6g/2h) Terminal Adapter: No Endurance: E2 (90 cycles@50%) SOCI: Ventilation: Independent

Filter:

Lateral Plug:

## STD. DIMENSIONS

 Length (mm  $\pm$  2):
 510

 Width (mm  $\pm$  2):
 218

 Height (mm  $\pm$  2):
 225

 Total Weight (kg  $\pm$  5%):
 43.00

PLUGS

Type: 6 x M27 BLACK

No

HANDLES

Type: 2 x Rope (Rigid holder) BLACK

**OTHERS** 

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.