


CUSTOMER DATASHEET


Printed: 11/02/2022


Product Management Transportation Europe

G34080M10-A 11/06/2010 Central Article Code: Created:

03/05/2018 Local Code: TJ050C Modified:







Final Outlook G3410-A Approval date 01/11/2010

	PERFORMANC	ES			
Voltage (V):	12 V				
C20 (Ah):	50.0	20 h			
Cranking (A):	800	EN			
Charge:	CHARGE	CHARGED			
Technology:	Orbital				
Grid:	Pb-Sn				
Vibration:	V3+ (30H	V3+ (30Hz+/-2Hz/6g/60h)			
Endurance:	E3 (144 c	E3 (144 cycles@50%)			

Type:	G34	BLACK	
Hold Down:	B7		
LID Adoptor	No		

CONTAINER

COVER

H.D. Adapter: No

Type: Maxxima/Orbital BLACK Polarity: ETN 1

Terminals: SAE M 3/8"- 5/16" taper&stud

Terminal Adapter: No SOCI: No Ventilation: Central 2 Filters Filter: Lateral Plug: No

	1EN		

Length (mm ± 2): 260 Width $(mm \pm 2)$: 173 Height (mm ± 2): 206 Total Weight (kg ± 5%): 17.90

PLUGS

6 x Valve+Cover BLACK Type:

HANDLES

2 x Integrated BLACK Type:

OTHERS

Degassing Tube: No

3/8-5/16 nuts in plastic bag

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.