


CUSTOMER DATASHEET


Printed: 11/02/2022


Product Management
Transportation Europe

Central Article Code: L01050C18-C Created: 08/03/2021

Local Code: TL550 Modified: 22/03/2021







Final Outlook L0118-C Approval date 01/11/2019

PERFORMANCES		CONTAINER
Voltage (V):	12 V	Type: L01 BLACK
C20 (Ah):	55.0 20 h	Hold Down: B13
Cranking (A):	540 EN	H.D. Adapter: No
Charge:	WET	COVER
Technology:	Vented/Flooded	Type: Double with Integrat BLACK
Grid:	Ca/Ca	Polarity: ETN 0
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals: EN taper post
Endurance: EN-EFB Requirement		Terminal Adapter: No
		SOCI: No

STD. DIMENSIONS				
Length (mm ± 2):	207			

Width (mm \pm 2): 175 Height (mm \pm 2): 190 Total Weight (kg \pm 5%): 14.10

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Ventilation:	Central		
Filter:	2 Filters		
Lateral Plug:	Standard shape	Left side	BLACK

PLUGS					
Type:	1 x Vent Sealed PSL-OE	ha BLACK			
HANDLES					
Type:	1 x PSL OE Integrated	BLACK			

OTHERS

Degassing Tube: No

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.