


CUSTOMER DATASHEET


Printed: 11/02/2022


Product Management Transportation Europe

D23052C17-A 28/10/2009 Central Article Code: Created:

Modified: 26/05/2021 Local Code: TL604







Final Outlook C2317-A Approval date 15/01/2010

PERFORMANCES				
Voltage (V):	12 V			
C20 (Ah):	60.0	20 h		
Cranking (A):	520	EN		
Charge:	WET			
Technology:	Vented/Flooded			

Grid: Ca/Ca

Vibration: Manufactured Specific

Endurance: Toyota Requirement (MHF)

H.D. Adapter:	No	
COVER		

CONTAINER

BLACK

Type: Flat/Screw Integrate BLACK

D23

B₀

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

6 x M18

STD. DIMENSIONS

Length (mm ± 2): 230 Width $(mm \pm 2)$: 173 Height (mm ± 2): 222 Total Weight (kg ± 5%): 16.20

Type:

Type:

Type:

Hold Down:

BLACK

HANDLES

PLUGS

1 x Integrated BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.