



## Yuasa Scheda Tecnica

### Yuasa YBX3053 - Batterie YBX3000 SMF

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Prestazione

Tensione	12V
Capacità (20 ore)	45Ah
Corrente di spunto A (EN1)	400A

#### Dimensioni

Lunghezza	238mm
Profondità	129mm
Altezza	225mm

#### Pesi e Misure

Peso medio con acido	12.4kg
----------------------	--------



#### Caratteristiche del Monoblocco

Tipo di monoblocco	JIS B24
Fissaggi alla base	N
Indicatore dello stato di carica	✓
Maniglie	✓
Circuito di sfiato	✓
Tipo di coperchio	Doppio Coperchio SMF


#### Tecnologia

Pastiglia antideflagrante	✓
Tecnologia	Ca/Ca
Separatore	PE
Test antiribaltamento VDA	✓
Corrente di carica raccomandata	3A
Performance Marking	W3-C2-V2-E1


#### Tipologia dei terminali

##### T1/T3


Standard DIN Post



Remove T1 adapter for T3



#### Schema di Collegamento



#### Fissaggio batteria

Scheda tecnica prodotta su E&OE



## Yuasa Technical Data Sheet

### Yuasa YBX3053 - YBX3000 SMF Batteries

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	400A

#### Dimensions

Length	238mm
Width	129mm
Height	225mm

#### Weights & Measures

Mean Weight with Acid	12.4kg
-----------------------	--------



#### Container Features

Case Type	JIS B24
Hold Down	N
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid

#### Technology

Flame Arrestor Technology	✓
Separator	Ca/Ca
VDA Roll Over Test	PE
Recommended Charge Rate	✓
Performance Marking	3A
	W3-C2-V2-E1


#### Terminal Type

##### T1/T3


Standard DIN Post



Remove T1 adapter for T3



#### Cell Assembly Layout



#### Battery Hold-down

Data Sheet generated on 07/09/2021 – E&OE