



## Yuasa Scheda Tecnica

### Yuasa YBX5005 - Batterie YBX5000 Silver High Performance SMF

#### Prestazione

Tensione	12V
Capacità (20 ore)	65Ah
Corrente di spunto A (EN1)	580A

#### Dimensioni

Lunghezza	232mm
Profondità	175mm
Altezza	225mm

#### Pesi e Misure

Peso medio con acido	16.2kg
----------------------	--------



#### Caratteristiche del Monoblocco

Tipo di monoblocco	D23 JIS
Fissaggi alla base	N
Indicatore dello stato di carica	✓
Maniglie	✓
Circuito di sfiato	✓
Tipo di coperchio	Doppio Coperchio SMF

#### Tecnologia

Pastiglia antideflagrante	✓
Tecnologia	Ca/Ca
Separatore	PE
Test antiribaltamento VDA	✓
Corrente di carica raccomandata	4A
Performance Marking	W4-C2-V3-E1



#### Tipologia dei terminali

#### Schema di Collegamento

#### Fissaggio batteria

#### T1

Standard DIN Post



Scheda tecnica prodotta su E&OE



## Yuasa Technical Data Sheet

### Yuasa YBX5005 - YBX5000 Silver High Performance SMF Batteries

#### Performance

Voltage	12V
Capacity (20-hour)	65Ah
Cold Cranking Amps (EN1)	580A

#### Dimensions

Length	232mm
Width	175mm
Height	225mm

#### Weights & Measures

Mean Weight with Acid	16.2kg
-----------------------	--------



#### Container Features

Case Type	D23 JIS
Hold Down	N
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid


#### Technology

Flame Arrestor Technology	✓
Separator	Ca/Ca PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W4-C2-V3-E1

#### Terminal Type

##### T1


Standard DIN Post



Positive Terminal

Negative Terminal

#### Cell Assembly Layout



#### Battery Hold-down



Data Sheet generated on 07/09/2021 - E&OE